

**The emlite EMP1 Three phase metering range offers high quality accurate meters that are suitable for direct connected domestic, commercial, Solar PV and light industrial applications.**

### Features -

- Fully MID approved
- 4 quadrant power measurement (Import and Export, Active and Reactive Energy)
- Optional Power Quality Information - Volts, Current, Power etc.
- Optional pulsed outputs
- Optical communications port
- Solid brass terminals



The EMP1.az and EMP1.av are the entry models of the emlite three phase metering range. They are suitable for a host of different applications where basic consumption or generation metering is required. The EMP1.az and EMP1.av variants covered in this information sheet are of solid high quality construction and benefit from features normally found in more expensive metering.

- Accuracy Class A or B (MID) [active energy] and Cl 2 [reactive energy\*]
- 4 quadrant energy measurement
- Optional power quality information\*
- Configurable pulsed outputs\*\*
- Multiple terminal cover options (Short, Extended( Standard), Extended
- Clear easy to read 8 digit LCD with specific symbols for different quantities.
- Solid Brass terminals
- Optional finger guard for main terminals

NB: \* denotes standard setting, \*\* pulse set for kWh import as standard

**EMP1.AV only**

**Pulsed Output**

An opto-isolated pulse output can provide data for collection by an energy management system or AMR data logger. These pulses are output via the meter's auxiliary terminals.

The output conforms to IEC 62053-31.



**Technical Data - Meter**

**Electrical**

Voltage	Nominal voltage	3 x 230v
	Voltage withstand	400V continuously
Frequency	Nominal frequency	50Hz, variation ± 5%
Current	Basic current (Iref)	5, 10, 15 and 20*
	Maximum (Imax)	100A

**Metrology**

Accuracy	Active energy	Class B, to EN 50470 1-3*
----------	---------------	---------------------------

**Environmental**

Temperature Range	-25°C to +55°C
-------------------	----------------

Ingress protection	IP54, to BS EN 60529
--------------------	----------------------

**Physical**

Terminal arrangement	DIN43857-Part 2, fixing centres of 150±1mm
----------------------	--

Main Terminal size	8.2mmø ± 0.2
--------------------	--------------

Terminal Construction	Solid brass
-----------------------	-------------

**Dimensions**

